

PANOLIN® +

Swiss Oil Technology

PANOLIN Sprays
The complete range



PANOLIN® +
Swiss Oil Technology

PANOLIN
CH-8322 Madetswil
Tel. +41 (0)44 956 65 65
Fax +41 (0)44 956 65 75
www.panolin.com
info@panolin.com

PANOLIN sprays for all applications

PANOLIN SPECIAL GREASE SPRAY

Prod. No. 59000, 500 ml



Fully synthetic, universal lubricating grease with excellent adhesion properties and extreme water resistance.

Applications: sleeve, roller and articulated bearings, screw-drives, universal joints, guide rollers, etc.

Temperature range: -30 °C to 120 °C.

Also available as:

bulk grease «PANOLIN SPECIAL GREASE», Prod. No. 74050.

PANOLIN MULTILUBE SPRAY

Prod. No. 59020, 500 ml



Colourless universal lubricant spray with excellent penetration and adhesion properties.

Applications: machinery and precision-mechanics, joints and couplings, door locks and hinges, etc.

Temperature range: -30 °C to 180 °C.

PANOLIN CHAINLUBE SPRAY

Prod. No. 59040, 500 ml



Transparent rapidly biodegradable chain lubricant spray with excellent penetration and adhesion properties.

Applications: chain link bearings, roller and ball bearings, gear and worm drives, all types of joints and couplings, etc.

Temperature range: -35 °C to 200 °C.

PANOLIN ZMO GREASE SPRAY

Prod. No. 59060, 500 ml



Black viscous-adhesive bituminous lubricating grease with excellent emergency running properties

Applications: Chain conveyors, open drives, gearwheels, racks, and swivelling cranes.

Temperature range: -30 °C to 150 °C, emergency running up to 400 °C.

PANOLIN PENLUBE SPRAY

Prod. No. 59200, 500 ml



Universal lubricating oil with good rust-loosening and penetration properties.

Applications: Hinges and links, bolts and pins, threads, door locks, etc.

Also available as:

bulk liquid «PANOLIN PENLUBE», Prod. No. 53050.

PANOLIN BRAKE CLEANER SPRAY

Prod. No. 59300, 750 ml



For cleaning and degreasing metals, glass and ceramic

Applications: particularly for brake parts and discs.

PANOLIN SILICONE H1 SPRAY

Prod. No. 59410, 500 ml



Antistatic universal dust-repellent preservation agent containing silicon.
Applications: for the care and protection of plastic and rubber parts.

Temperature range: up to 250 °C.

Nonfood Compounds
Program Listed H1
Registration 127 621

PANOLIN FORM H1 SPRAY

Prod. No. 59700, 500 ml



Silicon-free lubricant and parting agent.
Tasteless and compatible with beer foam.

Temperature range: -35 °C to 220 °C.

Nonfood Compounds
Program Listed H1
Registration 123 619

PANOLIN TEF OIL H1 SPRAY

Prod. No. 59730, 500 ml



Universal light-coloured PTFE oil spray.

Applications: for lubricating guide-rails, drives and sleeves.

Temperature range: up to 250 °C.

Nonfood Compounds
Program Listed H1
Registration 136 567

PANOLIN TEF GREASE H1 SPRAY

Prod. No. 59750, 500 ml



White PTFE aluminium-complex soap based lubricating grease.

Applications: general lubrication.

Temperature range: -10 °C to 120 °C (briefly up to 180 °C).

Nonfood Compounds
Program Listed H1
Registration 124 240

PANOLIN CL 60 SPRAY

Prod. No. 59790, 100 ml

New!



Rapidly biodegradable universal lubricating spray.

Applications: general lubrication.

Biodegradability acc. to OECD 301 B: > 60 %

Temperature range: -30 °C to 120 °C.

Nonfood Compounds
Program Listed H1
Registration 147 084

Part of the PANOLIN concept
GREENMACHINE®



All the sprays on this page are NSF registered.
They are suitable for the food, pharmaceuticals and animal feed industries.

Spray can matrix

- Primary application
- Secondary application

General application recommendations
Follow manufacturer's instructions

	PANOLIN SPECIAL GREASE	PANOLIN MULTILUBE	PANOLIN CHAINLUBE	PANOLIN ZMO GREASE	PANOLIN PENLUBE	PANOLIN BRAKE CLEANER	PANOLIN SILICONE H1	PANOLIN FORM H1	PANOLIN TEF OIL H1	PANOLIN TEF GREASE H1	PANOLIN CL 60
Greasing points	■									■	
General lubrication		■							■	■	■
Electrical contacts/battery poles		■			■						
Rustloosening and penetration oil		■	■		■				■		
Protection of plastic and rubber parts							■				
Brake cleaner/degreaser						■					
Conveyor chains and links		■	■		■				■	■	
Open gear drives and toothed rings				■							
Forming oils							■	■			
Against weld spatter							■	■			
Food/beverage/fodder/cosmetics and pharmaceuticals industries							■	■	■	■	■

PANOLIN[®]
Swiss Oil Technology 

PANOLIN
CH-8322 Madetswil
Tel. +41 (0)44 956 65 65
Fax +41 (0)44 956 65 75
www.panolin.com
info@panolin.com

SWISS TS
ISO 9001
ISO 14001 